

# IMPRESORA TERMICA ON 315 PLUS



## CARACTERISTICAS:

- Impresión de alta velocidad (250mm / seg.)
- Multi interfaces:
  - Serial + USB + Ethernet
  - Paralela + USB
- Compatible con EPSON ESC/POS y STAR (set de comandos)
- Aviso de fin de papel y detección de marca negra.
- Windows X86/X64 / Linux / OPOS driver
- Cambio de IP vía Serial o USB
- Recuperación de impresión automática cuando se desconecta la red.
- Conexión a cajón de dinero



USB

SERIAL

ETHERNET

CASHDRAWER PORT



POWER PORT

USB

PARALLEL

CASHDRAWER PORT

POWER PORT



# IMPRESORA TERMICA ON 315 PLUS

## ESPECIFICACIONES:

Printing	Print method	Direct thermal line
	Print width	64/72mm
	Dot density	512/576dot/line
	Print speed	250mm/s
	Interface	Serial +USB + Ethernet + Parallel +USB port
	Paper diameter	83mm
	Line space	3.75mm(can be adjustive)
	Character Size	ANK Font Font A: 12×24dots Font B: 9×17dots Simplified/Traditional Chinese Character: 24×24dots
Barcode	Code page	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/ Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/ Latvian/Arabic/PT151,1251/PC737/WPC1257/Thai Vietnam/PC864/ PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/( PC864)/ (Vietnam)/(Thai)
	Barcode mode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8) CODE39/ITF/CODABAR/CODE93/CODE128
	Fonts	GB18030
Buffer	Data	128K bytes
	NV Flash	256K bytes
Power	Cashdrawer out	DC 24V/1A
	Power supply	AC 110V/220V, 50~60Hz DC 24V/2A
Physical properties	Weight	1.651kg
	Dimension	145×186×140mm
Environment	Work environment	Temperature: 0~45°C, Humidity: 10~80%
	Storage environment	Temperature: -10~60°C, Humidity: 10~90%
Auto Cutter	Reliability	150km